

DATASHEET EX-series: EX500

A High-Performing, Affordable Endpoint Solution for Citrix, VMware Horizon, Microsoft, and NComputing Desktop Virtualization Platforms.

The **EX500** thin client is fully optimized for multiple virtualization platforms providing outstanding performance and value using the x86-64 CPU architecture. Features include 4K Ultra HD video, dual monitor ports, gigabit Ethernet, broad peripheral support and Wi-Fi all controlled by enterprise-grade device management software–a perfect platform for demanding knowledge workers across the organization.



Multi-platform optimization

The EX500 provides optimized multimedia capabilities for several virtualization platforms.

- **Citrix:** Virtual Apps and Desktops. Optimized for Microsoft Teams and supports Browser Content Redirection (BCR) to utilize local capabilities.
- VMware Horizon: VMware Blast and RDP support. Optimized for Microsoft Teams, and support Browser Content Redirection and local Multimedia Redirection (MMR) to utilize local capabilities.
- Microsoft: Support for Azure Virtual Desktop (AVD), Windows 365 Cloud PC, and Remote Desktop Services (RDS).
- **NComputing:** VERDE VDI, VERDE Remote Access and vSpace Pro Enterprise.

Powered by LEAF OS

LEAF OS is our small Linux-based operating system designed specifically for secure, highperformance access to virtual desktops and cloud workspaces. Flexible in its deployment, **LEAF OS** enables user access to multiple virtual desktop platforms from thin clients and personal computers.

PMC Endpoint Manager: Central management & express deployment

The **EX500** is easy to configure using PMC Endpoint Manager software. Remotely manage devices over local and wide-area networks including locations behind firewalls and NAT routers through an easy-to-use web-based user interface. Define multiple device profile configurations, push to individual or grouped devices, and schedule updates including firmware. A dashboard overview and detailed event log provide valuable information about your deployment. Easy-to-use for smaller organizations yet powerful enough to manage large cross-organizational deployments across multiple geographic locations, PMC simplifies.

Local application support

LEAF OS includes select local applications that run on the device, not through a virtualization platform. Direct access to the web via Chromium Browser eliminates virtualization lag. Microsoft Teams and Zoom both benefit from direct audio/video relay eliminating common concerns of web conferencing through virtual platforms. Additional 3rd party Linux applications can be installed in **LEAF OS** via the custom module support to further extend its functionality. **LEAF OS** controls the availability of these apps and their deployment method, with a Guest Mode option for Kiosk-like use.

EX500 Features

- Powered by Intel Quad-Core J3455 1.5 GHz (2.3 GHz Burst Frequency)
- 64GB eMMC and 4GB DDR SDRAM
- Optimized for Citrix HDX (Virtual Apps and Desktops), Microsoft (AVD, Windows 365, RDS) and NComputing (VERDE VDI, VERDE Remote Access, vSpace Pro Enterprise)
- Remotely manage endpoints via the web with PMC Endpoint Manager
- Local application support for direct access without a full VDI desktop
- Native dual monitor ports up to 3480x2160 @ 30hz
- USB 3.0 (2 ports) and USB 2.0 (2 ports) with transparent redirection
- 5GHz and 2.4GHz 802.11 b/g/n/ac Wi-Fi with Personal and Enterprise 802.1x security
- 10/100/1000 Ethernet (RJ45 port)
- Integrated VPN support (OpenVPN, OpenConnect, FortiClient, IPsec and PPTP)
- 3.5mm audio port (audio-in/out)

Hardware SKUs

 SKU: 700-0038 | EX500 with an activated LEAF OS perpetual license, 1-year Device AMP licensing coverage (software updates), and perpetual use of PMC Endpoint Manager.

Licensing SKUs

- SKU: NC-AMP-RXRDP-1A | Device AMP licensing is required after the first year to access software/firmware updates and support.
- SKU: vSpacePro-LeafOS | use EX500 with vSpace Pro Enterprise.



EX500 Cloud Ready Thin Client

Supported platforms:

Citrix

- Citrix DaaS
- · Citrix Virtual Apps and Desktops 7 1808 or newer
- Citrix StoreFront 3.0 or newer, StoreFront 1811 or newer (including connections through Citrix Gateways)
- Citrix XenApp/XenDesktop 7.6 or newer
- Citrix Web Interface 5.4

Microsoft

- Azure Commercial Cloud (Spring 2020 and Fall 2019)
- Azure U.S. Government Cloud
- Windows 365 Cloud PC
- Remote Desktop Services (RDS)
- Windows Server 2008 R2, 2012 R2, Multipoint Server 2012, 2016, 2016 Multipoint Services, 2019, 2022
- Windows 7, 8.1, 10, 11

VMWare

- VMware Horizon Cloud
- VMware Horizon 8 (2006 & later)
- VMware Horizon 7.13 & later

NComputing

- VERDE VDI and VERDE Remote Access version 8.2.7 or higher
- vSpace Pro Enterprise 12.5.2 or higher

EX500 Connections

HARDWARE	DESCRIPTION
KIT CONTENTS	1- EX500 access device, power supply, VESA mount kit, and a Quick Installation Guide.
SIZE	Width: 123 mm, Depth: 123 mm, Height : 22.8 mm
POWER CONSUMPTION	ldle/Sleep mode 5W / 2.5W
DISPLAY	Intel HD graphics 500 supporting resolutions up to 3840 x 2160 @ 30Hz in dual display mode. (2x HDMI ports)
CPU	Intel Celeron J3455 Quad-Core 1.5GHz (2.3 GHz Burst Frequency)
MEMORY	4GB DDR SDRAM
STORAGE	64GB eMMC
POWER	Power button (on/off)
NETWORK AND CONNECTIVITY	LAN (RJ-45 10/100/1000 Base-T)
	802.11 a/b/g/n/ac dual band WiFi module
AUDIO	3.5mm audio jack (audio in-out)
VIDEO RESOLUTIONS	Maximum hardware resolution (per HDMI port): 3480x2160 @ 30hz
	Platforms with lower maximum recommended resolutions: • Microsoft RDP & VERDE VDI : 2560x1600 • vSpace Pro Enterprise : 2560 x 1440
PERIPHERAL PORTS	USB 3.0 (2 ports) and USB 2.0 (2 ports). USB devices are transparently redirected providing support for mass storage, printers, scanners, smart card readers, headsets/speakers, webcams, COM ports, and 3D mice. Network-connected printers are also available.
MOUNT	VESA mount kit included
FIRMWARE MAINTENANCE	Firmware maintenance updates are included free for one year from date of EX500 device activation with a valid LEAF OS license.
WARRANTY	1 year hardware warranty included; Optional extended hardware warranty available
SOFTWARE	DESCRIPTION
OPERATING SYSTEM	NComputing LEAF OS (Linux)

EX-series products have been EMI certified according to FCC, CE, and KCC standards.



© Copyright 2023 NComputing Co., Ltd. NComputing® and vSpace® are internationally registered trademarks by NComputing. Copyright © 2003 – 2023. The product could differ from the images shown. The information contained herein is subject to change without notice. Specific features may vary from model to model. The only support and warranties for NComputing products and services are set forth in the express support and warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. NComputing shall not be liable for technical or editorial errors or omissions